



The **Ram ProMaster 3500 Windowed Van** delivers versatility and upfit compatibility, with **three wheelbases, four body lengths, three GVWRs and two roof heights**. Designed for a standard pallet, most models feature **side doors that open up to 49 inches wide, with rear doors that open to 260°**. The two interior heights max out at **6'4" inside** and the interiors offer up to **462.8 cu. ft.<sup>(14)</sup> of cargo capacity**. Engines include the award-winning **Pentastar V6, standard, or available 3.0L EcoDiesel I4**. This worker- and load-friendly front-wheel-drive engineering enables **low step-in height and minimal turning diameter**. ProMaster offers nearly 90° side walls, cavernous interior and three-piece modular front fascia enabling easy and fast service, along with **upfit-friendly architecture, low cost of ownership, ready-to-work electronic architecture, large windshield and exceptional interior comfort**.

## PRODUCT HIGHLIGHTS

### ALL PROMASTER MODELS

**3.6L Pentastar® V6 gas engine** mated to the 6-speed Automatic transmission – Standard

**3.0L EcoDiesel I4** mated to the 6-speed Dual-Active Drive transmission – Available

**Front-wheel-drive (FWD) transaxle** – Standard

**Towing:** 5,100 lb, all models<sup>(14)</sup>

### CARGO VAN MODELS

**3 weight classes:** 1500, 2500, 3500

**Wallet-friendly** oil change intervals; advised: 3.6L Pentastar V6 – 10,000 miles; 3.0L EcoDiesel I4 – 18,500 miles

**Total roof heights:** standard 88.7-inch; available 99.4-inch

**Load floor lengths:** 1500: 105- and 123-inch; 2500: 123- or 146-inch; 3500: 146- or 160-inch

**Cargo volumes:** 1500: 259.2-, 303.7- or 352.9-sq. ft.; 2500: 352.9- or 420.2-sq. ft.; 3500: 420.2- or 462.8-sq. ft.

**Payload:** 3,570 – 4,440-lb\* (depending on model and specifications)<sup>(14)</sup>

### CUTAWAYS/CHASSIS CAB MODELS

**RV/motor home suspension** – Available

**Wheelbase lengths:** 3500 class – 136-inch, 159-inch and 159-inch with Extended Frame

**Chassis Cab cab-to-axle lengths:** 81.1- and 104.1-inch

**Overall height:** 84.8-inch, all models

**Overall width:** 80.7-inch, all models (without mirrors)

**Back of cab to taillamp lengths:** 115.4-, 138.0- and 152.4-inch, depending on configuration

**Maximum payloads:** 4,420 – 5,160-lb,\*<sup>(14)</sup> based on model configuration

**Exterior mirrors** sized to accommodate upfit bodies up to 96 inches – Standard

**Taillamp wiring extension** – Standard

## SAFETY & SECURITY

**Electronic Stability Control (ESC)<sup>(3)</sup> system** includes Antilock Brake System (ABS), All-Speed Traction Control,<sup>(3)</sup> Brake Assist, Hill Start Assist, Rollover Mitigation, Trailer Sway Control (TSC)<sup>(3)</sup> – Standard

**“Follow-Me-Home” headlamp function**, with preset illumination – Standard

**Battery Saver**, shuts off all interior lighting after 15 minutes – Standard

## FEATURES

**Load floor height:** 21-inch (Cargo Van models)

**Turning diameter:** 36.3-ft (Short Wheelbase)

**High roof interior ceiling height:** 6'4" – Available (Cargo Van models)

**ParkView® Rear Back-Up Camera<sup>(5)</sup>** – Available

\*Specifications are based on 2016MY vehicle information.



Properly secure all cargo.

Body Type	Engines		Transmissions	
	3.6L Pentastar® DOHC VVT V6	3.0L Turbo EcoDiesel I4	6-speed Automatic	6-speed Dual-Active Drive*
Cargo Van	•	0	•	0
Windowed Van	•	0	•	0
Chassis Cab/Cutaway	•	0	•	0

• = Standard. 0 = Optional. \*Included with EcoDiesel engine.

## DIMENSIONS/SPECIFICATIONS<sup>(1)</sup>

Capability	Cargo Van						Windowed Van		
	1500		2500		3500		2500	3500	
	118" WB	136" WB	136" WB	159" WB	159" WB	159" WB, Extended	159" WB	159" WB, Extended	
	Standard Roof	Standard Roof	High Roof	High Roof	High Roof	High Roof	High Roof		
GVWR (lb)	8,550	8,550	8,550	8,900	8,900	9,350	9,350	8,900	9,350
GCWR (lb) Gas/Diesel	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500
Base Curb Weight (lb) Gas Engine	4,560	4,667	4,781	4,773	4,883	4,922	5,009	4,969	5,061
Base Curb Weight (lb) Diesel Engine	4,818	4,924	5,080	5,061	5,201	5,231	5,322	5,286	5,378
Maximum Payload (lb) Gas Engine*	3,990	3,880	3,760	4,120	4,010	4,420	4,340	3,930	4,280
Maximum Payload (lb) Diesel Engine*	3,730	3,620	3,460	3,830	3,690	4,110	4,020	3,610	3,970
Front GAWR (lb)	4,629	4,629	4,629	4,629	4,629	4,629	4,629	4,629	4,629
Rear GAWR (lb)	5,004	5,291	5,291	5,291	5,291	5,291	5,291	5,291	5,291
Curb-to-curb Turning (ft)	36.3	40.7	40.7	40.7	46.8	46.8	46.8	46.8	46.8
Maximum Towing <sup>†</sup> (lb)	5,100	5,100	5,100	5,100	5,100	5,100	5,100	5,100	5,100
<b>Dimensions</b>									
Body Height (in)	88.7	88.7	99.4	99.4	99.4	99.4	99.4	99.4	99.4
Overall Body Length (in)	195.4	213.1	213.1	213.1	236.0	236.0	250.5	236.0	250.5
Vehicle Width Without Mirrors (in)	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7	80.7
Vehicle Width With Mirrors Extended (in)	105.9	105.9	105.9	105.9	105.9	105.9	105.9	105.9	105.9
Cargo Body Overall Length (in)	105.1	122.8	122.8	122.8	145.9	145.9	160.2	145.9	160.2
Side Door Opening Width (in)	42.3	49.2	49.2	49.2	49.2	49.2	49.2	49.2	49.2
Side Door Opening Height (in)	58.5	58.5	69.0	69.0	69.0	69.0	69.0	69.0	69.0
Rear Doors Opening Width (in)	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5	61.5
Rear Doors Opening Height (in)	59.8	59.8	70.5	70.5	70.5	70.5	70.5	70.5	70.5
Maximum Cargo Volume (cu ft)	259.2	303.7	352.9	352.9	420.2	420.2	462.8	420.2	462.8

Chrysler, Ram, the Ram's Head logo, Pentastar and Uconnect are registered trademarks, and Ram ProMaster is a trademark of FCA US LLC. Bluetooth is a registered trademark of Bluetooth SIG, Inc. FCA US LLC reserves the right to make changes at any time, without notice or obligation. All product specifications are based on authorized information as of 4/1/16.

FLT-2017-0022

Capability	Chassis Cab			Cutaway		
	2500/3500	3500		2500/3500	3500	
	136" WB	159" WB	159" WB, Extended	136" WB	159" WB	159" WB, Extended
GVWR (lb)	8,900/9,350	9,350	9,350	8,900/9,350	9,350	9,350
GCWR (lb) Gas/Diesel	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500	11,500/12,500
Base Curb Weight (lb) Gas Engine	4,211	4,216	4,242	4,150	4,142	4,197
Base Curb Weight (lb) Diesel Engine	4,452	4,480	4,505	4,407	4,429	4,462
Maximum Payload (lb) Gas Engine*	4,680/5,130	5,130	5,100	4,740	5,200	5,150
Maximum Payload (lb) Diesel Engine*	4,440	4,870	4,840	4,490	4,920	4,880
Front GAWR (lb)	4,629	4,629	4,629	4,629	4,629	4,629
Rear GAWR (lb)	5,291	5,291	5,291	5,291	5,291	5,291
Curb-to-curb Turning (ft)	40.7	46.8	46.8	40.7	46.8	46.8
Maximum Towing <sup>†</sup> (lb)	5,100	5,100	5,100	5,100	5,100	5,100
<b>Dimensions</b>						
Body Height (in)	84.8	84.8	84.8	84.8	84.8	84.8
Overall Body Length (in)	207.0	230.0	244.4	207.0	230.0	244.4
Vehicle Width Without Mirrors (in)	80.7	80.7	80.7	80.7	80.7	80.7
Vehicle Width With Mirrors Extended (in)	105.9	105.9	105.9	105.9	105.9	105.9
Cab to Rear Axle <sup>‡</sup> (in)	81.1	104.1	104.1	81.1	104.1	104.1
Overhang Rear Axle to End of Frame** (in)	33.9	33.9	48.2	33.9	33.9	48.2

<sup>(1)</sup>Based on 2016MY vehicle information subject to change. \*Max payload based on body model, GVWR class. When properly equipped. <sup>†</sup>When properly equipped. <sup>‡</sup>Measured from center cab back to center of rear axle. \*\*Measured from center of axle to rear frame. Specifications subject to change. See dealer for most up-to-date information. WB = wheelbase.

<sup>(1)</sup>Always sit properly with the head restraint properly adjusted. Never place anything in front of the head restraint. <sup>(2)</sup>Always sit properly in the seat with the seat belt fastened. Children 12 and under should always be in a backseat correctly using an infant or child restraint system or with the seat belt positioned correctly for the child's age and weight. All occupants should always wear their lap and shoulder belts properly. <sup>(3)</sup>No system, no matter how sophisticated, can repeal the laws of physics or overcome careless driving actions. Performance is limited by available traction, which snow, ice and other conditions can affect. When the ESC warning lamp flashes, the driver needs to use less throttle and adapt speed and driving behavior to prevailing road conditions. Always drive carefully, consistent with conditions. Always wear your seat belt. <sup>(4)</sup>Always check visually for pedestrians and vehicles prior to proceeding or changing lanes. An electronic drive aid is not a substitute for conscientious driving. Always be aware of your surroundings. <sup>(5)</sup>When properly equipped.