



## 2022 Dodge Charger Pursuit SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.  
All dimensions are in inches (millimeters) unless otherwise noted.  
All dimensions measured at curb weight with standard tires and wheels.*

### GENERAL INFORMATION

Vehicle Type	E-segment sedan, all-wheel drive (AWD)
Assembly Plant	Brampton Assembly Plant, Ontario, Canada
EPA Vehicle Class	Large car
Introduction Date	2014 as a 2015 model (fleet customers only — <a href="http://www.fleet.chrysler.com">www.fleet.chrysler.com</a> )

### BODY AND CHASSIS

Layout	Longitudinal front engine, AWD
Construction	Unitized steel body and aluminum hood

### ENGINE: 3.6-LITER PENTASTAR® V-6

Availability	Standard
Type and Description	60-degree V-type, liquid-cooled
Displacement	220 cu. in. (3,604 cu. cm)
Bore x Stroke	3.78 x 3.27 (96.0 x 83.0)
Valve System	Chain-driven DOHC, 24 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum deep-skirt block with aluminum-alloy heads
Compression Ratio	10.2:1
Power	300 bhp (220.6 kW) @ 6,350 rpm (83.3 bhp/liter)
Torque	264 lb.-ft. (357.9 N•m) @ 4,800 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2; and E-85 (Federal Bin 5, 37 state compliant)
Oil Capacity	6 quarts (5.7 liters) with dry filter
Coolant Capacity	14 quarts (13.25 liters)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors and internal engine features <sup>1</sup>
EPA Fuel Economy mpg (city/hwy/combined)	18/26/21 <sup>2</sup>
Assembly Plant	Trenton South Engine Plant, Trenton, Michigan

# FCA | FLEET Product Info



## TRANSMISSION: TORQUEFLITE® EIGHT-SPEED AUTOMATIC

Availability	Standard
Description	Adaptive electronic control
Gear Ratios	
1st	4.71
2nd	3.14
3rd	2.10
4th	1.67
5th	1.29
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30 Standard
Final Drive Ratio	3.08 Standard
Overall Top Gear	2.06 Standard

## TRANSFER CASE

Availability	Standard
Type	Active, fully variable with front-axle disconnect
Center Differential	Planetary
Torque Split, Front/Rear	Fully variable

## ELECTRICAL SYSTEM

Alternator	220-amp — standard
Battery	H8 Case, 800 CCA AGM, maintenance-free

## SUSPENSION

Front	Independent SLA with high upper "A" arm, coil spring over gas-charged monotube shock absorbers and stabilizer bar
	Lateral and diagonal lower links with dual ball joint knuckles
Rear	Five-link independent with coil springs, gas-charged load-leveling NIVOMAT rear shocks, stabilizer bar and isolated suspension cradle

# FCA | FLEET Product Info



## STEERING

Type	Rack and pinion
	Electric power steering (EPS)
Overall Ratio	16.5:1
Turning Diameter (curb-to-curb)	38.7 ft. (11.8 m)
Steering Turns (lock-to-lock)	3.1

## DIMENSIONS AND CAPACITIES<sup>3</sup>

Wheelbase	120.2 (3,052)
Track, Front	63.4 (1,611)
Track, Rear	63.8 (1,620)
Overall Length	198.4 (5,040)
Overall Width	75.0 (1,905)
Overall Height	58.4 (1,482)
Ground Clearance	5.1 (130.0)
Frontal Area, sq. ft. (sq. m)	26.2 (2.43)
Drag Coefficient (Cd)	0.297
Curb Weight, lb. (kg)	4,338 (1,967.7)
Gross Vehicle Weight Rating (GVWR)	5,500 (2,495)
Gross Axle Weight Rating (GAWR)	2,850 (1,295)
Weight Distribution, percent F/R	53/47
Fuel Tank Capacity	18.5 gallons (70.0 liters)

# FCA | FLEET Product Info



## ACCOMMODATIONS<sup>3</sup>

Seating Capacity (front/second row)	2/3
Front	
Headroom	38.6 (980.4)
Legroom	41.8 (1,061.7)
Shoulder room	59.5 (1,511.3)
Hip room	56.2 (1,427.5)
Seat travel	Driver — 10.6 (269.2) Passenger — 8.66 (220)
EPA front row interior volume, cu. ft. (cu. m)	55.6 (1.574)
Rear Seat	
Headroom	36.6 (929.6)
Legroom	40.1 (1,019)
Knee clearance	3.9 (99)
Shoulder room	57.9 (1,470.7)
Hip room	56.1 (1,425)
EPA second row interior volume, cu. ft. (cu. m)	49.2 (1.393)
Total Interior Volume, cu. ft. (cu. m)	104.7 (2.965)
EPA Luggage Compartment Volume, cu. ft. (cu. m)	16.5 (0.467)
EPA Interior Volume Index, cu. ft. (cu. m)	121.2 (3.43)

## TIRES

Availability	Standard
Size and type	P225/60R18 99V BSW All-season performance
Mfr. and model	Goodyear performance tires
Revs per mile (km)	704 (437)
Availability	Optional
Size and type	P245/55R18 99W BSW All-season performance
Mfr. and model	Goodyear performance tires
Revs per mile (km)	705 (438)

# FCA | FLEET Product Info



## WHEELS

Availability	Standard
Type and material	Steel wheel with chromed center cap or optional painted wheel cover
Size	18 x 7.5

## BRAKES

Front	
Rotor size and type	14.5 x 1.26 (368 x 32) vented
Caliper size and type	1.77 (45) dual-piston sliding with cast-iron housing
Swept area	388 sq. in. (2,503.2 sq. cm.)
Rear	
Rotor size and type	13.8 x 1.02 (351 x 26) vented
Caliper size and type	1.78 (45) single-piston sliding with cast-iron housing
Swept area	300 sq. in. (1,935.5 sq. cm.)

## TRAILER TOWING

	Axle Ratio	Maximum Trailer Weight lbs. (kg) <sup>4</sup>
	3.07	1,000 (454 kg)

1. Meets Federal Tier 2 Bin 5 emission requirements and ULEV II requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington. 2. FCA-estimated mpg with 3.6L engine and eight-speed automatic transmission, AWD. Actual mileage may vary. 3. All dimensions are in inches unless otherwise noted and are measured at curb weight with standard tires. 4. When properly equipped. See dealer for details. ©2022 FCA US LLC. All Rights Reserved. Dodge and HEMI are registered trademarks of FCA US LLC.

Additional information and news from [media.stellantisnorthamerica.com](http://media.stellantisnorthamerica.com).

# # #